

# Buoyancy transmitter, Level, pneumatic, liquid level, interace level, liquid density measurement

167LP

### Main

Range of Product	Level
Product or Component Type	Buoyancy transmitter
Product Specific Application	Liquid level measurement Interface level measurement Density measurement
Kit composition	transmitter displacer element (to be purchased seperately))

## Complementary

Housing material	Aluminium
Pressure Rating	14.57251.9 psi (1500 bar)
Measurement accuracy	+/- 1 % of reading
Measurement range	010 m 030 ft
Type of measurement	Level inferred by buoyant force
Connector type	DIN flange ASME flange JIS flange

### **Environment**

Ambient air temperature for operation	-321932 °F (-196500 °C)
Ambient Air Temperature for Storage	-40194 °F (-4090 °C)
Product certifications	ATEX
IP Degree of Protection	IP55 IP65

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability

0	Environmental	£1:1
4	Environmental	tootbrint

Environmental Disclosure

Product Environmental Profile

#### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

### **Use Again**

○ Repack and remanufacture		
Take-back	No	